

BEFORE YOU BEGIN

Read these instructions and check to be sure all parts and tools are accounted. Please retain these installation instructions for future reference.

IMPORTANT

This Paddle Latch is exclusively designed for your vehicle. Please read the installation instructions thoroughly before beginning. Installation is easier if the vehicle is clean and free of debris.

INSTALLATION INSTRUCTIONS

- 1. Shift vehicle transmission into "PARK". Turn key to "OFF" position and remove from vehicle.
- 2. Product picture



3. Unscrew the surface of the tailgate first, then open the tailgate and unscrew the back of the gate. As shown below:





4. Remove the outer door panel, and remove the limit rods on both sides of the door panel and the door switch. Then replace the new switch with the original screws, and finally put the limit rods back in place. As shown below:

Paddle Latch for Polaris Ranger 900/570 Full-size

ZP-YJ-030503-107









5. Put the door panel with the new switch back on the original vehicle, and then tighten the screws that were removed before. As shown below:

Note: When installing door panels, the two limit rods must be threaded through the limit holes

on both sides of the door.







6. Installation finished.

Paddle Latch for Polaris Ranger 900/570 Full-size



ZP-YJ-030503-107



Note: Please refer to the installation video in the Amazon listing before your installation, or contact the seller for the installation video.